	М	Α	Т	E	R	Ι	Α	L	S	Α	F	E	Т	Y	D	Α	Т	A	S	Н	E	E	T

|-----|
| SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION |

THIS MATERIAL SAFETY DATA SHEET IS AVAILABLE IN SPANISH UPON REQUEST.

LOS DATOS DE SEGURIDAD DEL PRODUCTO PUEDEN OBTENERSE EN ESPANOL SI LO REQUIERE.

Product Name: ALLPRO PRO 40 SILICONIZED LATEX SEALANT  Revision Date: 03/16/2004 Page 2
SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS
Remaining ingredients are not considered hazardous per the OSHA Hazard Communication Standard.
Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); limits may vary between states. ** See Appendix C to 29 CFR 1910.1048 (Section II. A. 3.).
SECTION 3 - HAZARDS IDENTIFICATION
EMERGENCY OVERVIEW: A thick white or variously colored paste with a mild sweet odor.
WARNING! May cause eye, skin, nose, throat and respiratory tract irritation. Harmful if swallowed or absorbed through the skin. Presents little or no hazard (if spilled) and / or no unusual hazard if involved in a fire.
POTENTIAL HEALTH EFFECTS:
EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.
EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause allergic skin reaction or sensitization. Prolonged or repeated contact with skin may cause irritation.
EFFECTS OF OVEREXPOSURE - INHALATION: Vapor may cause nose, throat and respiratory tract irritation.
EFFECTS OF OVEREXPOSURE - INGESTION: Harmful if swallowed.
EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause skin, respiratory, kidney, cardiovascular and liver damage. Ethylene glycol has been shown to cause birth defects in laboratory animals.
MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: None known.
PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT, INHALATION, EYE CONTACT
SECTION 4 - FIRST AID MEASURES
EYE CONTACT: Immediately flood with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.
SKIN CONTACT: Wash thoroughly with soap and water.

(Continued on Page 3)

Product Name: ALLPRO PRO 40 SILICONIZED LATEX SEALANT Revision Date: 03/16/2004	Page 3
SECTION 4 - FIRST AID MEASURES	
INHALATION: Remove to fresh air. If you experience difficu breathing, leave the area to obtain fresh air. If continue difficulty is experienced, get medical attention immediatel	d breathing
INGESTION: DO NOT INDUCE VOMITING. Get medical attention i	mmediately.
COMMENTS: Call Medical Emergency 1-800-327-3874 if any irr complications arise from any of the above routes of entry.	itation or

|-----|

Product Name: ALLPRO PRO 40 SILICONIZED LATEX SEALANT

Revision Date: 03/16/2004 Page 4

j	SECTION	8 -	EXPOSURE	CONTROLS/PERSONAL	PROTECTION	

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels. A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

EYE PROTECTION: Wear safety glasses with side shields.

SKIN PROTECTION: Rubber gloves.

OTHER PROTECTIVE EQUIPMENT: None.

HYGIENIC PRACTICES: Wash contaminated clothing before reuse.

| SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : 210 - 220 F VAPOR DENSITY : Is heavier than air

ODOR : Slight ammonia

APPEARANCE : Colored paste EVAPORATION RATE: Is slower than Butyl

SOLUBILITY IN H2O: Negligible Acetate

SPECIFIC GRAVITY : 1.65-1.70 ph 8.0 - 8.8

VAPOR PRESSURE : 17 mm Hg @ 68 F.

PHYSICAL STATE : Paste

(See Section 16 for abbreviation legend)

|-----| | SECTION 10 - STABILITY AND REACTIVITY |

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Strong oxidizers and caustics.

 ${\tt HAZARDOUS\ DECOMPOSITION\ PRODUCTS:}\quad Normal\ decomposition\ products,\ i.e.\ COx,\\ NOx$ 

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

(Continued on Page 5)

Product	Name:	ALLPRO	PRO	40	SILICONIZED	LATEX	SEALANT		
Revision	n Date:	: 03/16	/2004	1				Page	5

١	
ĺ	SECTION 11 - TOXICOLOGICAL PROPERTIES
ĺ	

The toxicological properties of this material are unknown.

SIGNIFICANT DATA WITH POSSIBLE RELEVANCE TO HUMANS

This product contains trace amounts of free formaldehyde. OSHA, NTP and IARC identify formaldehyde as a potential carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, the significance of which to humans is unknown. There should be minimal risk when used with ventilation adequate to keep the atmospheric concentration of formaldehyde below the recommended exposure limit. Maintain adequate ventilation to prevent exposure above current OSHA / ACGIH exposure limits. Workplace monitoring of the air to define formaldehyde exposure levels may be necessary.

This product contains trace amounts of acrylonitrile. It is exempt from the OSHA acrylonitrile standard 29 CFR 1910.1045, paragraph (a) (2) (ii). Acrylonitrile has been classified by IARC as possibly carcinogenic to humans, by OSHA as carcinogenic and by NTP as reasonably anticipated to be a human carcinogen.

	   SEC"	TION 12 - ECOLOG	GICAL INFORMATION	
1	No Information.			
ĺ	SEC	TION 13 - DISPOS	SAL CONSIDERATIONS	

WASTE MANAGEMENT/DISPOSAL: Dispose of according to Federal, State, and Local Standards. This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulations, 40 CFR Section 261. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA WASTE CODE - If discarded (40 CFR 261): None.

l		
ĺ	SECTION 14 - TRANSPORTATION	INFORMATION

DOT PROPER SHIPPING NAME: Not Regulated by D.O.T.

DOT HAZARD CLASS: NONE

DOT UN/NA NUMBER: NONE PACKING GROUP: NONE

(Continued on Page 6)

Product Name: ALLPRO PRO 40 SILICONIZED LATEX SEALANT

Revision Date: 03/16/2004 Page 6

|-----|
| SECTION 15 - REGULATORY INFORMATION |

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

## SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

None

## TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12b if exported from the United States:

None

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME ----- CAS NUMBER

Acrylic polymer TSRN-618608-5059P

Water 7732-18-5

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME ----- CAS NUMBER
Acrylic polymer Proprietary
Water 7732-18-5

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are

known to the ss50 Tc 0.15 Tw ( ) Tj -450 -12 TD 0.15 Tc 0 Tw (Reau9Tc 0.15 Calif5 Tw T

Revision Date: 03/3					Page 7 
		5 - REGULATORY	_	-	 
Acrylonitrile		1	07-13-1		'
INTERNATIONAL REGULA	ATIONS: A	S FOLLOWS -			
CANADIAN WHMIS: This Product Regulations				-	controlled
CANADIAN WHMIS CLAS		_			
	GEGETO	N 16 OFFIED TO	XTD	17.037	i
HMIS RATINGS - HEAL	гн: 1	FLAMMABILITY	: 1	REACTIVITY: 0	
PREVIOUS MSDS REVIS	ION DATE:	Not Applicable	е		
VOC less water, less	s exempt	solvents: <35	gm/l(<4	18)	

LEGEND: ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

N.A. - NOT APPLICABLE N.E. -