



Stik-It Epoxy Putty

Material Safety Data Sheet

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Manufacturing Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents, and contractors of the information on the sheet.

SECTION I - GENERAL INFORMATION				
Black Swan Manufacturing Co. 4540 W. Thomas Street Chicago, IL 60651-3318 Telephone No: 1-773-227-3700 Fax No: 1-773-227-3705		For chemical emergencies during transportation only call INFOTRAC 1-800-535-5053 24 hours per day - 7 days a week		
Date Prepared 01/01/08		Trade Name STIK-IT EPOXY PUTTY		
SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION				
HAZARDOUS COMPONENTS	CAS#	APPROX%	ACGIH-TLV	OSHA-PEL
GLYCIDYL ETHERS OF BISPHENOL A RESINS	25068-38-6	13.05	N.E	N.E
TRI(DIMETHYLAMINOMETHYL)PHENOL	90-72-2	1.37	N.E	N.E
CRYSTALLINE SILICA	14808-60-7	12.64	N.E	N.E
*Title III Section 313 Supplier Notification: this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency planning and community Right-to-Know Act of 1976.				
19.6% GLYCIDYL ETHERS OF BISPHENOL A RESINS 1.37% TRI(DIMETHYLAMINOMETHYL)PHENOL 12.64% CRYSTALLINE SILICA				
19.6% GLYCIDYL ETHERS OF BISPHENOL A RESINS 1.37% TRI(DIMETHYLAMINOMETHYL)PHENOL 12.64% CRYSTALLINE SILICA				

NOT HAZARDOUS FOR SHIPPING PURPOSES.		REACTIVITY 0 2- MODERATE PROTECTIVE 3- SERIOUS EQUIPMENT A 4- SEVERE	
SECTION III - PHYSICAL DATA			
APPEARANCE PUTTY-LIKE	ODOR MILD AMINE ODOR	BOILING POINT N/A	
SPECIFIC GRAVITY (H2O=1) 1.5	VAPOR PRESSURE (mm Hg.) NIL	VOLATILE BY VOLUME (%) 0	
VAPOR DENSITY (AIR=1) N/A	EVAPORATION RATE (BUAC=1) NIL	SOLUBILITY IN WATER NONE	
SECTION IV - FIRE AND EXPLOSION HAZARD DATA			
FLASH POINT (METHOD USED)	FLAMMABLE LIMITS	LEL	UEL
NONE	(PERCENT BY VOLUME)	N/A	N/A
FIRE EXTINGUISHING MEDIA WATER SPRAY, FOAM, CO2, DRY CHEMICALS.			
SPECIAL FIRE FIGHTING PROCEDURES NONE			
UNUSUAL FIRE AND EXPLOSION HAZARD CO, ALDEHYDES, ACIDS, OXIDES OF SULFUR AND NITROGEN MAY BE FORMED.			
SECTION V - HEALTH HAZARD DATA			
PRIMARY ROUTES OR ENTRY			

EYE CONTACT: POSSIBLE IRRITANT AND SENSITIZER.

INGESTION: IRRITATION OF INTESTINAL TRACT.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

NONE.

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: INDUCE VOMITING.

SKIN CONTACT: WASH WITH SOAP AND WATER IMMEDIATELY.

EYE CONTACT: FLUSH WITH WATER CONSULT A PHYSICIAN.

SECTION VI - REACTIVITY

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	NONE

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE

HAZARDOUS DECOMPOSITION PRODUCTS

CO, ALDEHYDES, ACIDS, OXIDES OF SULFUR AND NITROGEN.

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	NONE

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SPILLS OR LEAKS: DISPOSE OF IN NORMAL MANNER; NOT A HAZARDOUS WASTE.

NOT A POTENTIAL POLLUTANT.

WASTE DISPOSAL METHOD

INCINERATE IN FURNACE OR BURY IN LANDFILL ACCORDING TO APPLICABLE REGULATIONS.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

Black Swan Mfg. Co. Telephone:773-227-3700 E-mail:
4540 W. Thomas Street
Chicago, IL 60651-3318