

M I y

C N C AN C M ANY N CA N

Con A yp

od c N CPS226588

Co p ny d n | | c | on

ChevronTexaco Global Lubricants

6001 Bollinger Canyon Rd.

San Ramon, CA 94583

United States of America

www.chevron-lubricants.com

n p o | on ncy pon

CHEMTREC: (800) 424-9300 or (703) 527-3887

ncy

ChevronTexaco Emergency Information Center: Located in the USA. International collect calls accepted.

(800) 231-0623 or (510) 231-0623

od c n o | on

email : lubemsds@chevrontexaco.com

In No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

n **on** No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

n **on** No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

N **o** **y** **q** **n** In an accident involving high-pressure equipment, this product may be injected under the skin. Such an accident may result in a small, sometimes bloodless, puncture wound. However, because of its driving force, material injected into a fingertip can be deposited into the palm of the hand. Within 24 hours, there is usually a great deal of swelling, discoloration, and intense throbbing pain. Immediate treatment at a surgical emergency center is recommended.

C **N** **N** **M** **A**

Leaks/ruptures in high pressure system using materials of this type can create a fire hazard when in the vicinity of ignition sources (eg. open flame, pilot lights, sparks, or electric arcs).

CLA **CA** **N**

OSHA Classification (29 CFR 1910.1200): Not classified by OSHA as flammable or combustible.

N **A** **A** **N** Health: 0 Flammability: 1 Reactivity: 0

L **A** **M** **M** **A** **B** **L**

w **p** **q** **n** (Cleveland Open Cup) 175 °C (347 °F) (Min)

A **o** **n** **on** No Data Available

l **y** **p** **o** **l** **l** **y** **o** **n** **l** Lower: Not Applicable Upper: Not Applicable

X **N** **N** **M** **A** Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

1 c m j o n y M

02=NTP Carcinogen

06=NJ RTK

07=PA RTK

No components of this material were found on the regulatory lists above.

Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the ANSI MSDS Standard (Z400.1) by the ChevronTexaco Energy Research & Technology Company, 100 Chevron Way, Richmond, California 94802.

▼ o | n o | o n | d o n | d o | o | o | n d | | d o | c o | c
o | d | o | n c | | n o | o n | y | p p | d n d | c o n d | | o n | y o n d o | c o n | o
n d | | o | o | y | n | | n d | n c | d | d | | n | o | d |
▼ o | y | o d | | c | | o n | o | o | n o | o n | d o n o | n y | p o n | | | y o
▼ o | | n o | o n | n | d | p o n | c o n d | | o n | | p | o n | c | | n | |
▼ | o | n d | | n | o n | o | | | | y o | | | o | | p | | c | p | p o