
Material Safety Data Sheet CHEVRO N Page 1 of 7

CHEVRON Hydraulic Oil AW ISO 68

•	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
<u> </u>	
•	
9.5	
~	
<u>*</u>	
)v	
	Å:
<del></del>	Ne
· · · · · · · · · · · · · · · · · · ·	<u> </u>
<b>^</b>	
,	
·	
	-
- -	
<b>\</b>	
T	
***	
<del></del>	<u> </u>
# <sub>10</sub>	

EYE: No first aid procedures are required. However, as a precaution flush eye with fresh water for 15 minutes. Remove contact lenses if worn. SKIN: No first aid procedures are required. As a precaution, wash skin MONG Number 90451

5



VAPOR DENSITY

NA (AIR=1): BOILING POINT: NA FREEZING POINT: NDA NA MELTING POINT:

Soluble in hydrocarbon solvents; insoluble in water. SOLUBILITY:

Ø.88 € 15.6/15.6C SPECIFIC GRAVITY:

EVAPORATION RATE: NA

E-e \_\_\_\_\_

VISCOSITY:

61.2 cSt € 40C (Min.)

PERCENT VOLATILE

(VOL):

NA

Revision Number: 4

Revision Date: 07/04/96


MSDS Number: 00451


E ~# Time.

7

- × ,

5





The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof ma У ity for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose. \*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*

\*\*\*\*\*\*\*\*\*\*\*\*\*