



The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont  
Material Safety Data Sheet

Page 1

-----  
"SUVA" 134a  
2187FR Revised 18-APR-2007  
-----

-----  
CHEMICAL PRODUCT/COMPANY IDENTIFICATION  
-----

Material Identification

Corporate MSDS Number : DU000693  
CAS Number : 811-97-2  
Formula : CH<sub>2</sub>FCF<sub>3</sub>  
CAS Name : "SUVA" 134a

Tradenames and Synonyms

HFC 134a  
VT1505

Company Identification

MANUFACTURER/DISTRIBUTOR  
DuPont Fluoroproducts  
1007 Market Street  
Wilmington, DE 19898

PHONE NUMBERS

Product Information : 1-800-441-7515 (outside the U.S.  
302-774-1000)  
Transport Emergency : CHEMTREC 1-800-424-9300(outside U.S.  
703-527-3887)  
Medical Emergency : 1-800-441-3637 (outside the U.S.  
302-774-1000)

-----  
COMPOSITION/INFORMATION ON INGREDIENTS  
-----

Components

Material	CAS Number	%
ETHANE, 1,1,1,2-TETRAFLUORO- (HFC-134a)	811-97-2	100

-----  
HAZARDS IDENTIFICATION  
-----

Potential Health Effects

INHALATION

ETHANE, 1,1,1,2-TETRAFLUORO-

## (HAZARDS IDENTIFICATION - Continued)

Gross overexposure may cause: Central nervous system depression with dizziness, confusion, incoordination, drowsiness or unconsciousness. Irregular heart beat with a strange sensation in the chest, "heart thumping", apprehension, lightheadedness, feeling of fainting, dizziness, weakness, sometimes progressing to loss of consciousness and death. Suffocation, if air is displaced by vapors.

## SKIN CONTACT

## ETHANE, 1,1,1,2-TETRAFLUORO-

Immediate effects of overexposure may include: Frostbite, if liquid or escaping vapor contacts the skin.

## EYE CONTACT

## ETHANE, 1,1,1,2-TETRAFLUORO-

"Frostbite-like" effects may occur if the liquid or escaping vapors contact the eyes.

## ADDITIONAL HEALTH EFFECTS

## ETHANE, 1,1,1,2-TETRAFLUORO-

Increased susceptibility to the effects of this material may be observed in persons with pre-existing disease of the: central nervous system, cardiovascular system.

## Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

-----  
FIRST AID MEASURES  
-----

## First Aid

## INHALATION

If high concentrations are inhaled, immediately remove to fresh

## (FIRST AID MEASURES - Continued)

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

## INGESTION

Ingestion is not considered a potential route of exposure.

## Notes to Physicians

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should only be used with special caution in situations of emergency life support.

-----  
FIRE FIGHTING MEASURES  
-----

## Flammable Properties

Flash Point : No flash point

Flammable Limits in Air, % by Volume:

LEL : None per ASTM E681

UEL : None per ASTM E681

Autoignition : >743 C(>1369 F)

## Fire and Explosion Hazards:

Cylinders may rupture under fire conditions. Decomposition may occur.

Contact of welding or soldering torch flame with high concentrations of refrigerant can result in visible changes in the size and color of torch flames. This flame effect will only occur in concentrations of product well above the recommended exposure limit, therefore stop all work and ventilate to disperse refrigerant vapors from the work area before using any open flames.

HFC-134a is not flammable in air at temperatures up to 100 deg. C (212 deg. F) at atmospheric pressure. However, mixtures of HFC-134a with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. HFC-134a can also become combustible in an oxygen enriched environment

## (FIRE FIGHTING MEASURES - Continued)

Experimental data have also been reported which indicate combustibility of HFC-134a in the presence of certain concentrations of chlorine.

**Extinguishing Media**

Use media appropriate for surrounding material.

**Fire Fighting Instructions**

Cool tank/container with water spray. Self-contained breathing apparatus (SCBA) may be required if cylinders rupture or release

## (HANDLING AND STORAGE - Continued)

Valve protection caps and valve cutlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point. Do NOT drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Never attempt to lift cylinder by its cap. Use a pressure reducing regulator when connecting cylinder to lower pressure (>3000 psig) piping or systems. Do NOT heat cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.

Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Storage area temperatures should not exceed 125 deg F (52 deg C) and should be free of combustible materials. Avoid area where salt or other corrosive materials are present. Avoid excessive inventory and storage time. Use a first-in first-out system. Keep accurate inventory records.

-----  
EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

## Engineering Controls

Normal ventilation for standard manufacturing procedures is generally adequate. Local exhaust should be used when large amounts are released. Mechanical ventilation should be used in low or enclosed places. Refrigerant concentration monitors may be necessary to determine vapor concentrations in work areas prior to use of torches or other open flames, or if employees are entering enclosed areas.

## Personal Protective Equipment

Impervious gloves and chemical splash goggles should be used when handling liquid.

Under normal manufacturing conditions, no respiratory protection is required when using this product.

Self-contained breathing apparatus (SCBA) is required if a large release occurs.

## Exposure Guidelines



## (STABILITY AND REACTIVITY - Continued)

## Polymerization

Polymerization will not occur.

-----  
TOXICOLOGICAL INFORMATION  
-----

## Animal Data

ETHANE, 1,1,1,2-TETRAFLUORO-

## EYE:

A short duration spray of vapor produced very slight eye irritation.

## SKIN:

Animal testing indicates this material is a slight skin irritant, but not a skin sensitizer.

## INHALATION:

4 hour, ALC, rat: 567,000 ppm.

Single exposure caused: Cardiac sensitization, a potentially fatal disturbance of heart rhythm associated with a heightened sensitivity to the action of epinephrine.

Lowest-Observed-Adverse-Effect-Level for cardiac sensitization: 75,000 ppm. Single exposure caused: Lethargy. Narcosis.

Increased respiratory rates. These effects were temporary.

Single exposure to near lethal doses caused: Pulmonary edema.

Repeated exposure caused: Increased adrenals, liver, spleen weight. Decreased uterine, prostate weight. Repeated dosing of higher concentrations caused: the following temporary effects - Tremors. Incoordination.

## CARCINOGENIC, DEVELOPMENTAL, REPRODUCTIVE, MUTAGENIC EFFECTS:

In a two-year inhalation study, HFC-134a, at a concentration of 50,000 ppm, produced an increase in late-occurring benign testicular tumors, testicular hyperplasia and testicular weight. The no-effect-level for this study was 10,000 ppm. Animal data show slight fetotoxicity but only at exposure levels producing other toxic effects in the adult animal. Reproductive data on male mice show: No change in reproductive performance. Tests have shown that this material does not cause genetic damage in bacterial or mammalian cell cultures, or in animals. In animal testing, this material has not caused permanent genetic damage in reproductive cells of mammals (has not produced heritable genetic damage).

-----  
ECOLOGICAL INFORMATION  
-----

## Ecotoxicological Information

AQUATIC TOXICITY:  
48 hour EC50 - Daphnia magna: 980 mg/L.  
96 hour LC50 - Rainbow trout: 450 mg/L

-----  
DISPOSAL CONSIDERATIONS  
-----

## Waste Disposal

Contaminated HFC-134a can be recovered by distillation or removed to a permitted waste disposal facility. Comply with Federal, State, and local regulations.

-----  
TRANSPORTATION INFORMATION  
-----

## Shipping Information

DOT/IMO  
Proper Shipping Name : 1,1,1,2-TETRAFLUOROETHANE  
Hazard Class : 2.2  
UN No. : 3159  
DOT/IMO Label : NONFLAMMABLE GAS

## Shipping Containers

Tank Cars.  
Tank Trucks.  
Ton Tanks.  
Cylinders.

-----  
REGULATORY INFORMATION  
-----

## U.S. Federal Regulations

TSCA Inventory Status : Reported/Included.

## TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312

Acute : Yes  
Chronic : Yes  
Fire : No  
Reactivity : No  
Pressure : Yes

## HAZARDOUS CHEMICAL LISTS

SARA Extremely Hazardous Substance: No  
CERCLA Hazardous Substance : No  
SARA Toxic Chemical : No



-----  
OTHER INFORMATION  
-----

## NFPA, NPCA-HMIS

NPCA-HMIS Rating  
Health : 1  
Flammability : 0  
Reactivity : 1

Personal Protection rating to be supplied by user depending on use conditions.

## Additional Information

MEDICAL USE: CAUTION: Do not use in medical applications involving permanent implantation in the human body. For other medical applications see DuPont CAUTION Bulletin No. H-50102.

-----  
The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsibility for MSDS : MSDS Coordinator  
> : DuPont Fluoroproducts  
Address : Wilmington, DE 19898  
Telephone : (800) 441-7515

# Indicates updated section.