Section 5 - Reactivity Data

Conditions To Avoid: Heat, sparks and open flame. Stability: Stable

Incompatability Avoid concentrated nitric and sulfuric acids, strong oxidizers, aldehydes and halogens.

(Materials To Avoid):

Hazardous Decomposition: Burning may produce carbon monoxide and carbon dioxide.

Hazardous Polymerization: Will not occur

Section 6 - Health Hazard Data

Routes of Entry Inhalation YES/Primary Skin YES/Primary Ingestion YES/Secondary

Health Hazards

Ingestion of large quantity may cause drowsiness and loss of consciousness.

NTP IARC NO Carcinogenicity OSHA Regulated NO NO

Signs And Symptoms of Exposure:

INGESTION: Slightly toxic. Ingestion of a large quantity may cause drowsiness and loss of consciousness. Stomach cramps, pain, nausea, vomiting and diarrhea may also occur. INHALATION: concentration may cause mild irritation of eyes, nose and throat. Concentration above the TLV may result in headache and drowsiness. SKIN CONTACT: No evidence of adverse effects from available information on skin absorption, but prolonged contact may cause drying and cracking of skin. EYE CONTACT: May cause slight to moderate irritation with possible corneal

Medical Conditions Generally Aggravated By Exposure:

See exposure.

Emergency And First Aid Procedures:

INGESTION: DO NOT INDUCE VOMITING. If conscious, dilute by giving large quantities of water or milk. Call a physician immediately. INHALATION: Remove to fresh air. If not breathing, give artificial respiration preferably mouth to mouth. If breathing is difficult, give oxygen. Call a physician. SKIN CONTACT: Wash the affected area with soap and water. Remove contaminated clothing. EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

Continued on Next Page

Steps To Be Taken In Case Material Is Released Or Spilled:



For Hercules Material Safety Data Sheets by fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.