

ULTRA PRO•MAX RED OXIDE PRIMER

HMIS RATING	
Health	1
Flammability	4
Reactivity	3

MATERIAL SAFETY DATA SHEET

NFPA 704 RATING	
NFPA 30B LEVEL	
3	

KIMBALL-MIDWEST
P.O. BOX 2470
COLUMBUS, OH 43216-2470
CORPORATE & EMERGENCY TELEPHONE: 800-424-9300

1. PRODUCT IDENTIFICATION

PART NUMBER 80-883
PRODUCT NAME ULTRAPRO•MAX RED OXIDE PRIMER
16OZ AEROSOL CAN
CHEMICAL FAMILY N/A
DOT SHIPPING Consumer Commodity ORM-D

2. HAZARDOUS INGREDIENTS

SPECIFIC CHEMICAL IDENTITY, COMMON NAMES	OSHA PEL	REL	ACGIH TLV	%
Acetone (67-64-1)	1000ppm	250ppm	750ppm	23.6
Propane (74-98-6)	1000ppm	1000ppm	2500ppm	12.6
*Toluene (108-88-3)	500ppm	150ppm	50ppm	7.4
N-Butane (106--97-8)	-	800ppm	800ppm	7.4
VM&P Naptha (64742-89-8)	-	-	-	5.9
Ethyl Alcohol (64-17-5)	1000ppm	1000ppm	1000ppm	3.9
Red Iron Oxide Pigment (1309-37-1)	6mg/m ³	10mg/m ³	-	3.8
*Xylene (1330-20-7)	100ppm	150ppm	150ppm	3.3
Talc (14807-96-6)	-	-	-	3.2
N-butyl Acetate (123-86-4)	150ppm	200ppm	200ppm	3.2
PM Acetate (108-65-6)	-	-	-	2.2
Mineral Spirits (64742-47-8)	-	-	-	1.9
Isobutyl Acetate (110-19-0)	150ppm	150ppm	150ppm	1.5
*Isopropyl Alcohol (67-63-0)	400ppm	500ppm	500ppm	1.1

All chemical compounds marked with an asterisk (*) are toxic chemicals subject to the reporting of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement.

3. PHYSICAL DATA

BOILING POINT (RANGE) -44°C (- 47°F)

KIMBALL
MIDWEST
Your Partner in Performance