

MATERIAL SAFETY DATA SHEET

MSDS 0496

=====
Section 1 -- PRODUCT AND COMPANY IDENTIFICATION
=====

	HMIS CODES	
PRODUCT NAME	Health	1
Nokorode Hot Weather Paste Flux	Flammability	1
	Reactivity	0
PRODUCT CODES	PPI	B
14800, 14820, 14830		
CHEMICAL FAMILY:		
Organic/Inorganic		
USE		
Soldering Flux		
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.	
The RectorSeal Corporation	Chemt	

respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

=====
Section 4 -- FIRST AID MEASURES
=====

-
- If INHALED: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.
 - If on SKIN: Immediately wash with soap and water. Remove and wash any contaminated clothing.
 - If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.
 - If SWALLOWED: If swallowed, call a physician immediately. Only induce

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

=====

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT:

N/A

Petrolatum

Food Chain Concentration Potential	N/D
WATERFOWL TOXICITY	N/D
BOD	N/D
AQUATIC TOXICITY:	N/D

=====
Section 13 -- DISPOSAL CONSIDERATIONS

Waste Classification: Non-regulated solid waste

Disposal Method: Approved landfill

Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

=====
Section 14 -- TRANSPORTATION INFORMATION
