MSDS No: OTH090E5
Issue Date: 10 June 2005

Page: 1 of 4

### MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Trade Name: OATEY PIPE/GASKET LUBE

Product Use: Lubricant for bell joint pipe gaskets.

Formula: See Section 2. Synonyms: Pipe lubricant.

Firm Name & OATEY CO. 4700 West 160th Street P.O. Box 35906 Cleveland,

Mailing Address: Ohio 44135, U.S.A. http://www.oatey.com

Oatey Phone Number: (216) 267-7100 or (800) 321-9532

Emergency Phone For Emergency First Aid call 1-303-623-5716 COLLECT. For Numbers: chemical transportation emergencies ONLY, call Chemtrec at

1-800-424-9300. Outside the U.S. 1-703-527-3887.

Prepared By: Corporate Director - Safety and Environmental Compliance

Preparation Date: June 10, 2005

## SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

Blend of soap and non-toxic ingredients:

%wt/wt: CAS NUMBER: ACGIH TLV TWA: OSHA PEL TWA: OTHER: INGREDIENTS: Potassium soap Conf. 61790-44-1 None None of fatty acid Mica Conf. 12001-26-2 3 mg/m3 20 mppcf None Propylene Glycol Conf. 57-55-6 None None None

Conf. = Confidential

OSHA Hazard Classification: Not hazardous

# SECTION 3 HAZARDS IDENTIFICATION

# EMERGENCY OVERVIEW

Amber paste with bland odor. May cause mild eye and skin irritation.

## SECTION 4 FIRST AID MEASURES

CALL 1-303-623-5716 COLLECT

Skin: Remove contaminated clothing immediately. Wash all exposed areas with

soap and water. Get medical attention if irritation develops.

Eyes: If material gets into eyes or if fumes cause irritation, immediately

flush eyes with plenty of water until chemical is removed. If

irritation persists, get medical attention immediately.

Inhalation: Not expected to be a normal route of exposure.

Ingestion: Drink water and call a poison control center or physician immediately.

Avoid alcoholic beverages. Never give anything by mouth to an

unconscious person.

## SECTION 5 FIRE FIGHTING MEASURES

Flashpoint / Method: > 220 Deg. F / > 104 Deg. C

Flammability: LEL = Not determined, UEL = Not determined.

MSDS No: OTH090E5
Issue Date: 10 June 2005
Page: 3 of 4

# SECTION 10 STABILITY AND REACTIVITY

MSDS No: OTH090E5 Issue Date: 10 June 2005

Page: 4 of 4

#### TRANSPORT INFORMATION SECTION 14

DOT Less than 1 Liter (0.3 gal) Greater than 1 Liter (0.3 gal)

Proper Shipping Name: Not hazardous under DOT transportation.

Hazard Class/Packing Group: Not applicable UN/NA Number: Not applicable

Hazard Labels:

IMDG

Proper Shipping Name: Not applicable Hazard Class/Packing Group: Not applicable UN Number: Not applicable Label: Not applicable

### SECTION 15 REGULATORY INFORMATION

Hazard Category for Section None

311/312:

Section 302 Extremely This product does not contain any chemicals regulated

Hazardous Substances (TPQ): under SARA Section 302.

Section 313 Toxic Chemicals: This product does not contain any chemicals regulated

under SARA Section 313

CERCLA 103 Reportable Report spills required under federal, state and local

Quantity: regulations.

California Proposition 65: This product does not contain any chemicals subject

to the California Proposition 65 regulation.

TSCA Inventory: All components of this product are on the TSCA

Inventory or are exempt.

Canadian WHIMS Classification: Not a controlled product. This product has been

classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS

contains all the information required by the CPR.

### SECTION 16 OTHER INFORMATION

NFPA and HMIS:

NFPA Hazard Signal: Health: 1 Flammability: 1 Reactivity: 0 Special: None

HMIS Hazard Signal: Health: 1 Flammability: 1 Reactivity: 0 PPE: B

## Disclaimer:

The information herein has been compiled from sources believed to be reliable, upto-date, and is accurate to the best of our knowledge. However, Oatey cannot give any guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use.