

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924
International Emergency: 813-348-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: SA9 BATTERY PROTECTOR & SEALER 5 OZ AE
Item No: 80370
Product Type: Aerosol coating

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
MINERAL OIL 8042-47-5	20-30	5 mg/m ³ TWA (oil mist)	5 mg/m ³ (oil mist)
PROPANE 74-98-6	15-25	simple asphyxiant; 2500 ppm TWA	1000 ppm TWA; 1800 mg/m ³ TWA
ACETONE 67-64-1	15-30	500 ppm TWA; 1188 mg/m ³ TWA	1000 ppm TWA; 2400 mg/m ³ TWA
XYLENE 1330-20-7	15-25	100 ppm TWA; 434 mg/m ³ TWA	100 ppm TWA; 435 mg/m ³ TWA
PETROLATUM 8009-03-8	10-20	Not Listed	Not Listed
ETHYL BENZENE 100-41-4	1-10	100 ppm TWA; 434 mg/m ³ TWA	100 ppm TWA; 435 mg/m ³ TWA

3. HAZARDS IDENTIFICATION

Toxicity: Aspiration hazard if swallowed. Deliberately concentrating and inhaling the vapor may be harmful or fatal. Exposure to vapors or mist may result in irritation of the respiratory tract. Long term exposure to

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C):

<0 degrees F. Based on propellant

Recommended Extinguishing Media:

Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures:

Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Oxides of carbon. Irritating vapors.

Hazardous Products Formed by Fire or Thermal Decomposition:

Unusual Fire/Explosion Hazards:

Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.

Lower Explosive Limit:

1.0

Upper Explosive Limit:

12.8

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F. Exposure to high temperatures may cause container to burst.

Handling:

Avoid contact with skin and eyes. Do not inhale vapors. Do not puncture or incinerate container. Do not use near heat, sparks or open flame. Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances, and other sources of ignition. Intentionally concentrating and

Product name: SA9 BATTERY PROTECTOR &
SEALER 5 OZ AE

Item 80370

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: