

MSDS - Material Safety Data Sheet

Product Name: TITE SEAL PAINTABLE AUTO BODY UNDERCOATING


MSDS No.: T1616

I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY

Address: 600 RADIATOR ROAD

City, ST Zip:



<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	

Health
Flammability
Reactivity
Pers. Protection



<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

MSDS - Material Safety Data Sheet

Product Name: TITE SEAL PAINTABLE AUTO BODY UNDERCOATING

MSDS No.: T1616

None Determined

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

MSDS - Material Safety Data Sheet

Product Name: TITE SEAL PAINTABLE AUTO BODY UNDERCOATING

MSDS No.: T1616

Personal Protective Equipment:

See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:

Boiling Point: N/A

Melting Point: N/A

Evaporation Rate (Butyl Acetate = 1): < 1

Vapor Pressure (mm Hg.): N/A

Specific Gravity (H2O = 1): 1.01730

Vapor Density (AIR = 1): > 1

Solubility In Water: Negligible

Appearance and Odor: Black wet film with solvent odor.

Other Information: Freeze Point: 32 F

Vapor Pressure: 55-75

VOC Content: 39.9%

X. Stability and Reactivity:

Stability:

Stable

Incompatibility (Materials to Avoid):

Incompatibility: Strong Acids, Alkalis, oxidizers, and amines.

Decomposition/By Products:

Carbon Monoxide, Carbon Dioxide

Hazardous Polymerization:

Will not occur

XI. Toxicological Information:

No data available.

XII. Ecological Information:

No data available

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

XIV. Transport Information:

DOT Hazard Class: ORM-D

Shipping Name: Consumer Commodity

XV. Regulatory Information:

MSDS - Material Safety Data Sheet

Product Name: TITE SEAL PAINTABLE AUTO BODY UNDERCOATING

MSDS No.: T1616

See Section 2 for SARA Reportable Chemicals.

USA TSCA: All components of this material are listed on the US TSCA Inventory.

NJ RTK

VM&P Naphtha 8032-32-4

Toluene 108-88-3

Methyl Acetate 79-20-9

XVI. Other Information:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye.
KEEP AWAY FROM CHILDREN AND ANIMALS!

N/E: Not Established

N/D: Not Determined

N/A: Not Applicable

N/AV: Not Available

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.