

MSDS

PRODUCT NAME: #1017-ZINC CHROMATE PRIMER
PRODUCT CODE: 000000000000001017

HMIS CODES: H C F R
3 * 3 1

===== [SECTION I - MANUFACTURER IDENTIFICATION] =====

MANUFACTURER'S NAME: RICHARDS PAINT COMPANY
ADDRESS : 200 PAINT STREET, ROCKLEDGE, FL 32955

EMERGENCY PHONE : 800-424-9300 DATE PRINTED : 6/13/05
INFORMATION PHONE : 321-636-6200 NAME OF PREPARER : RICHARD'S PAINT

===== [SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION] =====

MAPARORTABLEOMPANE S/S

VACANAMUMB

mm Hg @ TEMP

VAPERCE

MSDS

===== [SECTION V - REACTIVITY DATA] =====

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID:

Excessive heat, ignition sources, poor ventilation, corrosive atmospheres, excessive aging.

INCOMPATIBILITY:

Alkaline materials, strong acids and oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Lead and Chromium Oxides form when burned. Carbon dioxide, carbon monoxide, and various hydrocarbons.

===== [SECTION VI - HEALTH HAZARD DATA] =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Inhalation: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Eye contact: Severe irritation, redness, tearing and blurred vision.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Skin contact: Can dry and defat skin causing cracks, irritation and dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Contains Zinc Chromate & trace amounts of EthylBenzene. Symptoms include gastrointestinal irritation, nausea, and

MSDS

remove to disposal container. Observe all relevant federal, state and local laws.

WASTE DISPOSAL METHOD:

Consult local, state and federal hazardous waste regulations before disposing into approved hazardous waste landfills. Obey relevant laws. ** DO NOT INCINERATE CLOSED CONTAINERS **

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Use in well ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames.

OTHER PRECAUTIONS:

This product contains a toxic chemical(s) in quantities subject to the reporting requirements of Section 313 of Title III and 40 CFR 372. Employees should be trained in safety measures when using this product. Consult the most recent OSH Standards regarding exposure limits and health hazards which may not be covered in this Material Safety Data Sheet.

===== [SECTION VIII - CONTROL MEASURES] =====

RESPIRATORY PROTECTION:

Use in well ventilated area. If ventilation is inadequate, use of an OSHA approved respirator (negative pressure type) is recommended. If workplace overexposure limit is exceeded NIOSH/MSHA approved air supplied respirator is advised.

VENTILATION:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV.

PROTECTIVE GLOVES:

Wear resistant gloves such as nitrile rubber.

EYE PROTECTION:

Use chemical safety glasses, goggles or faceshields for eye protection.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of "head-caps" whenever possible is strongly recommended.

WORK/HYGIENIC PRACTICES:

Wash hands before eating, launder clothes before reuse. Eye wash and safety showers in the workplace is recommended.

===== [SECTION IX - DISCLAIMER] =====

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Richard's Paint Manufacturing Co. Inc. to be accurate at the time of preparation. Richard's Paint Manufacturing Co., Inc. does not assume any legal responsibility for use or reliance upon same. ** BEFORE USING ANY PRODUCT READ ITS LABEL **