

# MSDS

PRODUCT NAME: #620 - ALKYD EGG SHELL ENAMEL WHITE  
PRODUCT CODE: 0000000000000000620

HMIS CODES: H C F R  
2 2 0

===== [ SECTION I - MANUFACTURER IDENTIFICATION ] =====

MANUFACTURER'S NAME: RICHARDS PAINT COMPANY  
ADDRESS : 200 PAINT STREET, ROCKLEDGE, FL 32955

EMERGENCY PHONE : 800-424-9300 DATE PRINTED : 6/13/05  
INFORMATION PHONE : 321-636-6200 NAME OF PREPARER : RICHARD'S PAINT

===== [ SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ] =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg @	TEMP	PERCENT
ALIPHATIC HYDROCARBON (M.SPIRITS) OSHA PEL: 500 PPM, ACGIH TLV: 100 PPM	8052-41-3	3.1	68 F	25.1% TO 30.0%
* ETHYLBENZENE OSHA PEL-TWA: 100ppm / ACGIH TLV-TWA: 100ppm / ACGIH TLV-STEL: 125ppm	100-41-4	7.1	68 F	.08

(\*) Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.  
(&) Indicates this chemical is a known or suspected carcinogen. \*\* See Section VI, Health Hazard Data. \*\*

===== [ SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ] =====

BOILING RANGE: 0 deg F - 405 deg F WPG (H2O=8.33): 11.67 lb/g1

# MSDS

---

**INCOMPATIBILITY:**

Alkaline materials, strong acids and oxidizing agents.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS:**

Carbon dioxide, carbon monoxide, various hydrocarbons

===== [ SECTION VI - HEALTH HAZARD DATA ] =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:**

Inhalation: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:**

Eye contact: Severe irritation, redness, tearing and blurred vision.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:**

Skin contact: Can dry and defat skin causing cracks, irritation and dermatitis.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:**

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis. CALL PHYSICIAN IMMEDIATELY AND HAVE THE NAMES OF ALL INGREDIENTS AVAILABLE.

**HEALTH HAZARDS (Acute and Chronic):**

Inhalation: Dizziness, breathing difficulty, headaches and loss of coordination. Eye contact: Severe irritation, tearing, redness and blurred vision. Skin contact: Can dry and defat skin causing cracks, irritation and dermatitis. Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Chronic overexposure: Liver, kidney, testes, central nervous system and brain damage. EthylBenzene: - IARC has determined that there is inadequate evidence of the carcinogenicity of ethylbenzene in humans. IARC has determined that there is sufficient evidence for the carcinogenicity of ethylbenzene in experimental animals.

**\*\*\* CARCINOGENICITY \*\***

NTP CARCINOGEN: Yes

IARC MONOGRAPHS: Yes

OSHA REGULATED: Yes

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:**

Dermatitis, respiratory tract irritation.

**EMERGENCY AND FIRST AID PROCEDURES:**

Inhalation overexposure: Move person to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration and get medical attention. Eye contact: Flush with large quantities of water for 15 minutes. Skin contact: Wash thoroughly with soap and water. Remove contaminated clothing. Ingestion: Do not induce vomiting, can cause chemical pneumonitis and pulmonary edema. Contact a Physician immediately. If any symptoms persist get medical attention.

# MSDS

---

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:**

Use in well ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames.

**OTHER PRECAUTIONS:**

Smoking in area where material is used should be strictly prohibited.

===== [ SECTION VIII - CONTROL MEASURES ] =====

**RESPIRATORY PROTECTION:**

Use in well ventilated area. If ventilation is inadequate, use of an OSHA approved respirator(negative pressure type) is recommended. If workplace overexposure limit is exceeded NIOSH/MSHA approved air supplied respirator is advised.

**VENTILATION:**

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV.

**PROTECTIVE GLOVES:**

Wear resistant gloves such as nitrile rubber.

**EYE PROTECTION:**

Use chemical safety glasses, goggles or faceshields for eye protection.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of "head-caps" whenever possible is strongly recommended.

**WORK/HYGIENIC PRACTICES:**

Eye wash and safety showers in the workplace are recommended.

===== [ SECTION IX - DISCLAIMER ] =====

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Richard's Paint Manufacturing Co.Inc. to be accurate at the time of preparation. Richard's Paint Manufacturing Co., Inc. does not assume any legal responsibility for use or reliance upon same. \*\*  
BEFORE USING ANY PRODUCT READ ITS LABEL \*\*