

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: 90 Ceramic Adhesive
PRODUCT CODE: 90

HMIS CODES: H F R P
1 0 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: CHICAGO ADHESIVE PRODUCTS CO.
ADDRESS 1105 FRONTENAC ST.
AURORA, IL. 60504

EMERGENCY PHONE: 800-424-9300 DATE REVISED: 05/17/2004
INFORMATION PHONE: 630-679-9100 DATE PRINTED: 08/12/2005
NAME OF PREPARER: Michelle Kascak

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

COMPONENTS	CAS NUMBER	VAPOR PRESSURE	WEIGHT
		MM HG @ TEMP	PERCENT

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. Hazardous ingredients must be reported when present at 1.0% or greater.***

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING POINT: 212 Degrees F. SPECIFIC GRAVITY (H2O=1): 1.55
VAPOR DENSITY: Heavier than air. EVAPORATION RATE: Slower than Ether.
SOLUBILITY IN WATER: Soluble.
APPEARANCE AND ODOR: White paste - Mild sweet odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: NA METHOD USED: NA
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: NA UPPER: NA

EXTINGUISHING MEDIA: Will not support combustion.

SPECIAL FIRE FIGHTING PROCEDURES: None

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

===== SECTION V - REACTIVITY DATA =====

STABILITY: Stable

CONDITIONS TO AVOID: NA

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing agents and caustics

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Oxides of carbon if co-burned with flammable material.

HAZARDOUS POLYMERIZATION: Will not occur

VENTILATION: Local exhaust; Use with adequate ventilation. Open doors and windows to create cross ventilation during use and until adhesive dries.

PROTECTIVE CLOTHES/GLOVES: Impervious gloves

EYE PROTECTION: Safety goggles required

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required

WORK/HYGENIC PRACTICES: Thorough washing of skin with soap and water before eating, or drinking.

===== SECTION IX - SHIPPING INFORMATION =====

D.O.T. PROPER SHIPPING NAME: Adhesives

HAZARDOUS SUBSTANCE 49CFR CERCLA: NA

HAZARD CODE: NA

D.O.T. HAZARD CLASS: Not Regulated

D.O.T. LABELS REQUIRED: NA

testing to prove that these risks do not exist. These amounts are typical quantities and may be below the Proposition 65 level of concern, or could even be zero.

OSHA Standard 29CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, material safety data sheets, training and access to written records. We request that you and it is your legal duty to, make all information in this material safety data sheet available to your employees.

The Following ingredients are considered to be classified as per OSHA HazardCommunication Standard (29CFR1910.1200):

NA

===== SECTION X - DISCLAIMER INFORMATION =====

*****THE CRITERIA FOR LISTING COMPONENTS IN THE HAZARDOUS INGREDIENTS SECTIONS IS AS FOLLOWS: CARCINOGENS ARE LISTED WHEN PRESENT AT 0.1% OR GREATER; COMPONENTS WHICH ARE OTHERWISE HAZARDOUS ACCORDING TO OSHA ARE LISTED WHEN PRESENT AT 1.0% OR GREATER.**

While this information and recommendations set forth herein are believed to be accurate as of the date hereof, Chicago Adhesive Products Co. (CHAPCO) MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

The information contained within the MSDS is considered propriety and is a trade secret. Unauthorized distribution or duplication of this information is prohibited.