

MSDS

PRODUCT NAME: PLIOLITE /MASONRY COATING
PRODUCT CODE: SR-895

HMIS CODES: H C F R
2 2 0

===== [SECTION I - MANUFACTURER IDENTIFICATION] =====

MANUFACTURER'S NAME: RICHARDS PAINT COMPANY
ADDRESS : 200 PAINT STREET, ROCKLEDGE, FL 32955

EMERGENCY PHONE : 800-424-9300 DATE PRINTED : 6/13/05
INFORMATION PHONE : 321-636-6200 NAME OF PREPARER : RICHARD'S PAINT

===== [SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION] =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg @	TEMP	PERCENT
ALIPHATIC HYDROCARBON (M.SPIRITS) OSHA PEL: 500 PPM, ACGIH TLV: 100 PPM	8052-41-3	3.1	68 F	10.1% TO 15.0%
AROMATIC HYDROCARBON (NAPHTHA) OSHA PEL: 100 mg/M3, ACGIH TLV: 100 mg/M3, OTHER: 100 mg/M3	64742-95-6	4	68 F	10.1% TO 15.0%
DIETHYLENE GLYCOL MONOBUTYL ETHER	112-34-5	.02	68 F	< 5.0%

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

MSDS

CONDITIONS TO AVOID:

Excessive heat, poor ventilation, corrosive atmospheres, excessive aging.

INCOMPATIBILITY:

Alkaline materials, strong acids and oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Carbon dioxide, carbon monoxide, various hydrocarbons

===== [SECTION VI - HEALTH HAZARD DATA] =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Inhalation: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue,

MSDS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Use in well ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames.

OTHER PRECAUTIONS: