

MATERIAL SAFETY DATA SHEET

U.S. DEPARTMENT OF LABOR, OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION, HAZARD
COMMUNICATION STANDARD, 29 CFR 1910.1200

The Steco Corporation
2330 Cantrell Road
P.O. Box 2238
Little Rock, AR 72203

Emergency Response: (800) 255-3924
Information: (800)-643-8026
Fax #: (501) 374-4278
Date Reviewed: **March 1, 2006**
Current Date: November 7, 2007

TRADE NAME:
DOT SHIPPING NAME:
CHEMICAL NAME & SYNONYMS:
HMIS/NFPA CODE:
MANUFACTURING CODE NO.:
COMMODITY CODE NO.:

TAP MAGIC EP-XTRA® Formula
Not a Regulated Material
Petroleum Hydrocarbons and Additives
Health 1; Fire 1; Reactivity 1
8358
332-9150

I. HAZARDOUS INGREDIENTS

<u>Component</u>	<u>CAS #</u>	<u>OSHA PEL</u> <u>ppm</u>	<u>ACGIH TLV</u> <u>mg/m³</u>	<u>Other Limits</u> <u>Recommended</u>	<u>Max.%</u>
Chlorinated Paraffins	61788-76-9	*	N/A	---	<20

II. INGREDIENTS

Naphthenic Oils	64742-53-6	*	N/A	---	<80
Sulfurized Paraffins	64742-54-7	*	N/A	---	<5
Petroleum Sulfonic Acid Salt	68608-26-4	*	10	---	<5
Petroleum Olefins	64743-02-8	*	10	TWA 1 mg/m ³	<5

* These products do not have a unique regulatory limit, however, the OSHA Pel for mineral oil is 5 mg/m³

III. PHYSICAL DATA

SKIN CONTACT: Prolonged or repeated exposure may cause irritation.

INGESTION: Headache, drowsiness, nausea, fatigue.

EYE: May cause pain and irritation.

EFFECTS OF CHRONIC

OVEREXPOSURE : Same as for acute overexposure.

CARCINOGENICITY : Not a carcinogen or suspect carcinogen.

EMERGENCY AND FIRST-AID PROCEDURES **EYE:** Flush eyes gently with water for at least 15 minutes, forcibly holding eyelids open to ensure complete irrigation of all eye and lid tissue. See physician.

SKIN: Wash with soap and water. If rash or irritation persists, see physician.

INHALATION: Remove to fresh air. See physician if irritation persists. In case of exposure to fumes from fire, remove person to fresh air. If unconscious, have professional administer oxygen. If breathing stops, administer mouth to mouth resuscitation.

INGESTION: Do not induce vomiting. Call physician. If individual is conscious, give large quantities of water (milk if available). If vomiting occurs spontaneously, keep airway clear and give more water.

VI. REACTIVITY DATA

STABILITY: Stable at ambient temperatures and pressure. Elevated temperature and exposure to strong alkalis, oxidizers, and/or acids will promote decomposition. Such decomposition results in the release of hydrogen chloride, hydrogen sulfide, and sulfur from the product. At normal room temperatures, decomposition is virtually nil. Exposure to strong direct sunlight may cause decomposition and discoloration of some components present in this product.

INCOMPATIBILITY: Contact with alkali materials, oxidizers, or acids should be avoided.

HAZARDOUS DECOMPOSITION PRODUCTS: This product may release toxic fumes when burned; including but not limited to: hydrogen chloride, hydrogen sulfide, carbon monoxide, and short chain hydrocarbons.

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: None

VII. DISPOSAL, SPILL OR LEAK PROCEDURES

AQUATIC TOXICITY : Not Determined.

SPILL OR LEAK PROCEDURES **Small Spills:** Soak up with shop towels or absorbent material such as oil-dry or vermiculite. **Large Spills:** Any leaks should be stopped. Spill should be contained, then cleaned up using vacuum truck or absorbent material.

WASTER DISPOSAL METHOD **Dispose of in accordance with all local, state and federal regulations. "If inert absorbents are employed in spill containment or cleanup, these absorbents must be non-biodegradable materials if destined for landfill disposal. Suitable absorbents include natural minerals (clay), activated charcoal, man-made polymers (HD polyethylene)."**

NEUTRALIZATION CHEMICALS : N/A

VIII. SPECIAL PROTECTION INFORMATION

EYE PROTECTION : Standard eye protection should be worn when using this product.