

United States Gypsum Company 125 South Franklin Street Chicago, Illinois 60680-4124

EMICAL FAMILY: Acrylic Sealant

SECTION 2 COMPOSITION, INFORMAT

SECTION 3 HAZARD IDENTIFICATION (continued)

POTENTIAL HEALTH EFFECTS

ACUTE:

Eyes: Airborne mist, dust or direct contact can cause mechanical irritation of eyes. If burning, redness, itching, pain or other symptoms persist or develop, consult physician.

Skin: Direct, prolonged or repeated contact with the skin may cause irritation.

Inhalation: Inhalation of vapors may cause headache and nausea. Inhalation of mist when spray applying or dust created when sanding a surface coated with this product can irritate the nose, throat, and the upper respiratory tract. Persons subjected to large amounts of this dust will be forced to leave area because of nuisance conditions such as coughing, sneezing and nasal irritation. Labored breathing may occur after excessive inhalation. If respiratory symptoms persist, consult physician.

Ingestion: If ingested may cause gastrointestinal discomfort including nausea, vomiting, lethargy, and diarrhea and may be fatal.

CHRONIC:

Eyes: None known.

Skin: None known.

Ingestion: No known effects.

Inhalation: Exposures to respirable crystalline silica are not expected during the normal use of this product; however, actual levels must be determined by workplace hygiene testing.

Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. The risk of

USG FIRECODE® Brand Acrylic Firestop Spray Sealant

SECTION 5 FIRE FIGHTING MEASURES

General Fire Hazards:	Not expected to bur	rn.		
Extinguishing Media:	Water or use extinguishing media appropriate for surrounding fire.			
Special Fire Fighting Procedures:	Wear appropriate p	Wear appropriate personal protective equipment (See section 8).		
Unusual Fire & Explosion Hazards	None known			
Hazardous Combustion Products:	None known	_		
Flash Point: N	one Known	Auto Ignition:	Not Applicable	
M6lgnitih(u)09(d0-0.000 763.8521e4132 0.0 TD1e 3 of 8)TETq28.95.2(g)-0.8(fire.)JJTT2 1 Tf-18.4132 -1.3533 TD-0.0004 Tc-0				

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION (continued)

RESPIRATORY PROTECTION:

Wear a NIOSH/MSHA-approved respirator in poorly ventilated areas, and if TLV is exceeded. A respiratory program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

OTHER PERSONAL PROTECTIVE EQUIPMENT:

Eye/Face: Wear safety glasses, goggles or face shield for eye protection.

Skin: Wear neoprene gloves. Wear adequate clothing to minimize skin contact. Wash clothing on a regular basis. **General:**





USG FIRECODE® Brand Acrylic Firestop Spray Sealant

SECTION 16 OTHER INFORMATION (continued)

NIOSH	National Institute for Occupational Safety and Health
MSHA	Mine Safety and Health Administration
OSHA	Occupational Health and Safety Administration
ACGIH	American Conference of Governmental Industrial Hygienists
IARC	International Agency for Research on Cancer
DOT	United States Department of Transportation
EPA	United States Environmental Protection Agency
NFPA	National Fire Protection Association
HMIS	Hazardous Materials Identification System
PPE	Personal Protection Equipment
TSCA	Toxic Substances Control Act
DSL	Canadian Domestic Substances List
NDSL	Canadian Non-Domestic Substances List
SARA	Superfund Amendments and Reauthorization Act of 1986
RCRA	Resource Conservation and Recovery Act
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act of 1980
UN/NA#	United Nations/North America number
CFR	Code of Federal Regulations
WHMIS	Workplace Hazardous Material Information System

Prepared by:

Product Safety USG Corporation 125 South Franklin St. Chicago, Illinois 60606

END