

HMIS RATING	
Health	1
Flammability	4
Reactivity	3

## MATERIAL SAFETY DATA SHEET

NFPA 704 RATING	
NFPA 30B LEVEL	
3	

KIMBALL-MIDWEST  
P.O. BOX 2470  
COLUMBUS, OH 43216-2470  
CORPORATE & EMERGENCY TELEPHONE: 800-424-9300

### 1. PRODUCT IDENTIFICATION

PART NUMBER ..... 80-880  
PRODUCT NAME ..... ULTRA PRO• MAX GLOSS WHITE PAINT  
16OZ AEROSOL CAN  
CHEMICAL FAMILY ..... N/A  
DOT SHIPPING ..... Consumer Commodity ORM-D

### 2. HAZARDOUS INGREDIENTS

SPECIFIC CHEMICAL IDENTITY, COMMON NAMES	OSHA PEL	REL	ACGIH TLV	%
Acetone (00067-64-1)	1000ppm	250ppm	750ppm	17.8
Propane (00074-98-6)	1000ppm	1000ppm	2500ppm	15.7
Titanium Dioxide (13463-67-7)	-	-	-	11.9
N-Butane (00106-97-8)	-	800ppm	800ppm	9.3
Barium Sulfate (07727-43-7)	5mg/m <sup>3</sup>	5mg/m <sup>3</sup>	10mg/m <sup>3</sup>	5.0
*Methyl Iso-butyl Ketone (00108-10-1)	100ppm	75ppm	75ppm	4.8
Gycol Ether EP (02807-30-9)	-	-	-	4.8
Isobutyl Acetate (110-19-0)	150ppm	150ppm	150ppm	4.8
Methyl Propyl Ketone (00107-87-9)	200ppm	150ppm	250ppm	3.4
*Xylene (01330-20-7)	100ppm	150ppm	150ppm	2.4

All chemical compounds marked with an asterisk (\*) are toxic chemicals subject to the reporting of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement.

### 3. PHYSICAL DATA

BOILING POINT (RANGE) ..... -44°C (-47°F)  
VAPOR PRESSURE PSIG @ 70°F ..... 8300.00 hPa  
VAPOR DENSITY (AIR = 1) ..... N/A  
SOLUBILITY IN WATER ..... Slight  
SPECIFIC GRAVITY (H2O = 1) ..... 0.8725  
MELTING/FREEZING POINT ..... N/A  
EVAPORATION RATE (Ether=1) ..... >1  
VOC content (by weight) ..... 46%  
APPEARANCE AND ODOR ..... White liquid/Aromatic

### 4. FIRE AND EXPLOSION DATA

FLASH POINT ..... -19°C (-2°F)  
UPPER EXPLOSIVE LIMIT (%) ..... 13.0%  
LOWER EXPLOSIVE LIMIT (%) ..... 1.7%  
EXTINGUISHING MEDIA ..... Extinguishing powder, CO<sub>2</sub>, Sand. Do not use water!  
SPECIAL FIREFIGHTING PROCEDURES ..... Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.  
FIRE AND EXPLOSION HAZARDS ..... Vapors may form explosive mixture with air.  
NFPA Flammability Hazard ..... 4

### 5. HEALTH EFFECTS DATA

#### SHORT TERM EFFECTS OF EXPOSURE

ROUTE OF ENTRY ..... Skin absorption, Inhalation, Ingestion, Eye contact, Skin contact  
HEALTH HAZARDS (ACUTE AND CHRONIC) .....  
EYE CONTACT ..... Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of a fine dust in the eyes.  
INGESTION ..... This material may be harmful or fatal if swallowed. Irritating to mouth, throat or stomach.  
INHALATION ..... Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor. Prolonged inhalation may be harmful.  
SKIN CONTACT ..... Generally does not irritate the skin.

### 5. HEALTH EFFECTS DATA (CONT'D)

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE ..... Heart disease, respiratory disorders.

#### FIRST AID PROCEDURES

EYE CONTACT ..... Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.  
SKIN CONTACT ..... Wash with soap and water. Get medical attention if irritation develops or persists.  
INGESTION ..... If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.  
INHALATION ..... Remove to fresh air; seek immediate medical attention; if breathing stops, begin artif831H1

**KIMBALL  
MIDWEST**  
*Your Partner in Performance*