

UNELKO CORPORATION

14641 N 74TH STREET
SCOTTSDALE, AZ 85260
FAX: (480) 483-7674

Information & Emergency Phone: (480) 991-7272

IN CASE OF TRANSPORTATION EMERGENCY, CONTACT CHEM-TEL, INC. 800-255-3924

MATERIAL SAFETY DATA SHEET

1. PRODUCT INFORMATION

TRADE NAME: ELIMINATE® SHOWER, TUB & TILE CLEANER
PRODUCT DESCRIPTION: Bathroom Cleaner
REVISION DATE: 04/19/05

2. COMPOSITION / INGREDIENTS INFORMATION

HAZARDOUS INGREDIENTS

| <u>MATERIAL or COMPONENT</u> | <u>CAS #</u> | <u>EEC#</u> | <u>TLV (UNITS)</u> | <u>APPROX.%(WGT)</u> |
|---------------------------------|-------------------|-------------|--------------------|----------------------|
| Ethylene Glycol Monobutyl Ether | 111-76-2203-905-0 | | 20.0 ppm | 2.8% |

NON-HAZARDOUS INGREDIENTS

| | | | | |
|----------------------------|-------------|--|-----|------|
| Sodium Xylene Sulfonate | 1300-72-7 | | N/A | 1.0% |
| Cocoamidopropylbetaine | 61789-39-7 | | N/A | 0.5% |
| Anionic Surfactant Complex | Proprietary | | N/A | 5.8% |

3. HAZARDOUS IDENTIFICATION

HEALTH HAZARD: May cause irritation to eyes if contacted by composition.

4. FIRST AID MEASURES

EYE CONTACT: Flush with water for 15 minutes. Seek medical attention if irritation develops.

5. FIRE FIGHTING MEASURES

FLAMMABILITY: Product is not classified as flammable.

6. ACCIDENTAL RELEASE MEASURES

Mop or soak up spillages in absorbent material to collect and contain for disposal. Dispose of in accordance with Local Authority Regulations.

7. HANDLING AND STORAGE

HANDLING: Local exhaust needed to maintain levels below TLV. Use only in accordance with label instructions.
Avoid contact with eyes.

STORAGE: Store at temperatures below 49°C. Keep container closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Use designated respiratory equipment when TLV limits are exceeded.

EYE PROTECTION: Eye protection is recommended when transferring bulk quantities.

SKIN PROTECTION: Use rubber gloves when transferring bulk quantities.

9. PHYSICAL DATA (Product)

| | |
|--|-----------------------------|
| BOILING POINT, °C | 100°C |
| MELTING POINT, °C | N/A – Not Determined |
| APPEARANCE @ 25°C | Liquid |
| FLASH POINT, °C (TAG OPEN CUP, ASTM D-1310) | NONE |
| AUTO-IGNITION TEMPERATURE, °C | N/A – Not Determined |
| EXPLOSIVE LIMITS, VOL% IN AIR | N/A – Not Determined |
| SOLUBILITY IN WATER @ 25°C | SOLUBLE |
| VAPOUR PRESSURE @ 25°C, mm HG | 25 |
| VAPOUR DENSITY, (AIR=1) | >1 |
| EVAPORATION RATE (BUTYL ACETATE=1) | 1.0 |