

MATERIAL SAFETY DATA SHEET:E-Z CUT

DATE OF ISSUE: 12/11/2002

SUPERCEDES: 11/02/2001

SECTION I - GENERAL INFORMATION**Chemical Name & Synonyms:**

N/A

Trade Name & Synonyms:

E-Z CUT

Chemical Family:

EMULSIFIABLE PETROLEUM

Formula Mixture: X**Manufacturer's Name:**

Partsmaster, Div of NCH Corp.

Address:

P.O. Box 225830

Dallas, TX 75265-5830

Prepared By:

C Williamson/Chemist

Product Code Number

0055

Emergency Phone Number

800-424-9300

SECTION II - HAZARDOUS INGREDIENTS

SECTION IV - FIRE AND EXPLOSION HAZARD

Flash Point:	Flammable Limits:	LEL:	UEL:
180°F / SETAFLASH	DEGBE	0.85	24.6

Extinguishing Media:

Foam:X	Alcohol Foam:X	CO2:X	Dry Chemical:X	Water Spray:	Other:
--------	----------------	-------	----------------	--------------	--------

Special Fire Fighting Procedures:

FIREFIGHTERS SHOULD WEAR A SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY TO PREVENT BURSTING.

Unusual Fire and Explosion Hazards:

THE USE OF WATER SPRAY (FOG) WHILE EFFECTIVE, MAY CAUSE FROTHING AND FOAMING. NEVER USE A WATER JET AS THIS WILL JUST SPREAD THE FIRE. USE CARE AS SPILLS MAY BE SLIPPERY.

NFPA Hazard Rating: (0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)

Health:3	Flammability:1	Instability:0	Special:
----------	----------------	---------------	----------

SECTION V - HEALTH HAZARD DATA**Threshold Limit Value:**

NOT ESTABLISHED FOR MIXTURE. SEE SECTION II.

Effects of Overexposure:**-Acute(Short Term Exposure)**

EYE CONTACT: CAUSES SEVERE IRRITATION SEEN AS STINGING, TEARING, REDNESS AND A BURNING SENSATION. PROLONGED CONTACT MAY CAUSE BURNS, CORNEAL DAMAGE AND POSSIBLE BLINDNESS. SKIN CONTACT: CAUSES IRRITATION SEEN AS ITCHING AND REDNESS; MAY CAUSE ALLERGIC SKIN REACTION SEEN AS DELAYED SKIN RASH WHICH MAY BE FOLLOWED BY BLISTERING, SCALING AND OTHER SKIN EFFECTS. INHALATION: CAUSES RESPIRATORY IRRITATION SEEN AS COUGHING AND SNEEZING. WITH INHALATION AT LOW LEVELS, NO HARMFUL EFFECTS ARE EXPECTED. AT HIGH VAPOR CONCENTRATIONS, INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS SUCH AS HEADACHE, DIZZINESS DROWSINESS, WEAKNESS, UNCONCIOUSNESS AND POSSIBLE ANESTHETIC EFFECTS FROM CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION: CAUSES IRRITATION WITH POSSIBLE NAUSEA, VOMITING AND DIARRHEA. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS SUCH AS HEADACHE, DIZZINESS, WEAKNESS, STAGGERING GAIT, NAUSEA, BLURRED VISION, EXCITATION AND IN EXTREME CASES COMA OR DEATH.

-Chronic (Long Term Exposure)

MAY CAUSE SKIN SENSITIZATION IN SOME INDIVIDUALS. ON RARE OCCASIONS, PROLONGED AND REPEATED EXPOSURE TO OIL MIST POSES A RISK OF CHRONIC LUNG INFLAMMATION. THIS CONDITION IS USUALLY ASYMPTOMATIC AS A RESULT OF REPEATED SMALL ASPIRATIONS. SHORTNESS OF BREATH AND COUGHING ARE THE MOST COMMON SYMPTOMS. ASPIRATION MAY LEAD TO PULMONARY EDEMA AND HEMORRHAGE AND MAY BE FATAL. SIGNS OF LUNG INVOLVEMENT INCLUDE INCREASED RESPIRATION AND HEART RATES AS WELL AS A BLUISH DISCOLORATION OF THE SKIN. CHRONIC SKIN CONTACT MAY PROMOTE DERMATITIS AND OIL ACNE. IN RARE CASES, AN INCREASED SENSITIVITY TO SUNLIGHT (PHOTOSENSITIVITY) MAY OCCUR. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE ARE PRE-EXISTING RESPIRATORY AND SKIN CONDITIONS SUCH AS ASTHMA, EMPHYSEMA AND DERMATITIS. TARGET ORGANS: BLOOD-FORMING ORGANS AND CENTRAL NERVOUS SYSTEM.

Primary Routes of Entry:	Inhalation:X	Ingestion:	Absorption:X
---------------------------------	--------------	------------	--------------

Emergency and First Aid Procedures:**-Inhalation:**

REMOVE FROM THE AREA TO FRESH AIR. SEEK MEDICAL ATTENTION IF RESPIRATORY IRRITATION DEVELOPS OR IF BREATHING BECOMES DIFFICULT.

-Eye Contact:

IMMEDIATELY RINSE THE EYES WITH WATER. REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING FOR AT LEAST 15 MINUTES. HOLD THE EYELIDS APART TO ENSURE RINSING OF THE ENTIRE SURFACE OF THE EYES AND LIDS WITH WATER. GET IMMEDIATE MEDICAL ATTENTION.

-Skin Contact:

WASH AFFECTED AREAS WITH LARGE AMOUNTS OF SOAP AND WATER FOR 15 MINUTES. REMOVE CONTAMINATED CLOTHING AND SHOES. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. WASH CLOTHING AND CLEAN SHOES BEFORE REUSE.

-Ingestion:

GIVE 3 TO 4 GLASSES OF WATER, BUT DO NOT INDUCE VOMITING. IF VOMITING OCCURS, GIVE FLUIDS AGAIN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR CONVULSING PERSON.

-Notes to Physician:

THERE IS NO SPECIFIC ANTIDOTE. TREAT THE PATIENT SYMPTOMATICALLY.

SECTION VI - TOXICITY INFORMATION**Product Contains Chemicals Listed as Carcinogen or Potential Carcinogen By:**

IARC: No **NTP:** No **OSHA:** No **ACGIH:** No **OTHER:** No

VOC CONTENT: 31.4% BY WEIGHT; 31.7% BY VOLUME; 293.7 G/L

DIETHYLENE GLYCOL MONOBUTYL ETHER

ORL-RAT LD50: 6.56 G/KG, TIME TO DEATH: 1-7 DAYS, MAJOR SIGNS: NARCOSIS 4.

SKN-RBT LD50: 4.12 ML/KG 4.

SKN-RBT: UNOCCLUDED CONTACT 0.01 ML, NO IRRITATION AT 24 HR 4.

EYE-RBT: SEVERE IRRITATION 4.

IHL-RAT SATURATED VAPOR STUDIES 8HR, MORTALITY: 0/6 4.

IN A TWO-WEEK DERMAL STUDY WITH RATS, REPORTED IN LITERATURE, 1900 MG/KG/DAY OR HIGHER OF DIET

IN A 30-DAY DRINKING WATER STUDY WITH RATS, A DOSAGE OF 0.6 GM/KG RESULTED IN REDUCED GROWTH A

IN THE HUMAN PATCH TEST, 1 OF 10 SUBJECTS HAD DEFINITE ERYTHEMA. 4.

SEVERELY HYDROTREATED HEAVY NAPHTHENIC PETROLEUM DISTILLATES

ORL-RAT LD50: > 5000 MG/KG 3.

SKN-RBT LD50: > 5000 MG/KG 3.

SKN-RBT SDT: 500 MG SEVERE 3.

MINERAL OIL MISTS DERIVED FROM HIGHLY REFINED OILS ARE REPORTED TO HAVE LOW ACUTE AND SUB-ACUT

THESE PETROLEUM DISTILLATES ARE SEVERELY HYDROTREATED, SEVERELY SOLVENT EXTRACTED AND/OR PROCE

POLYOLEFIN ANHYDRIDE

ORL-RAT LD50: >5000 MG/KG 3.

SKN-RBT LD50: >2000 MG/KG 3.

CHLORINATED PARAFFIN

ORL-RAT LD50: > 21500 uL/KG 3.

SKN-RBT LD50: > 10 ML/KG 3.

SKN-RAT SDT: 100 MG/24H MILD 3.

EYE-RBT SDT: 100 MG MILD 3.

IARC HAS DETERMINED THAT CHLORINATED PARAFFINS OF AVERAGE CARBON-CHAIN LENGTH C12 AND AVERAGE :

2-AMINO-2-METHYL-1-PROPANOL (AMP)

ORL-RAT LD50: 2900 MG/KG 3.
 IHL-RAT TCl₀: 230 uG/M3/4H/13W-I 3.
 SKN-RBT LD50: >2000 MG/KG 4.
 SKN-RBT: SCORE OF 6.37; SEVERE 4.
 EYE-RBT: SCORE OF 110 UNDILUTED; SEVERE
 30 SEC APPLICATION/30 SEC WASH: SCORE OF 89.3
 15 SEC APPLICATION/30 SEC WASH: SCORE OF 69.3 4.
 SKN-RBT: 1000, 1500, 2000 MG/KG;
 24HR - SEVERE IRRITATION AND BLACK; 2-3 DAYS - NECROTIC;
 14 DAYS - ESCHAR FORMATION 4.

SULFURIZED RAPE OIL

ORL-RAT LD50: >5000 MG/KG 4.
 IHL-RAT: 1365 MG/M3 4.
 SKN-RBT: NON-IRRITATING 4.
 EYE-RBT: NON-IRRITATING 4.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

EYE-HMN SDT: 8 MG MILD 3.
 EYE-RBT SDT: 500 MG/24H MILD 3.
 SKN-RBT OPEN IRRITATION TEST: 500 MG MILD 3.
 SKN-RBT LD50: 10 ML/KG 3.
 ORL-RAT LD50: 5400 uL/KG 3.

ETHYLDIHYDRO-1H,3H,5H-OXAZOLO (3,4-C)-OXAZOLE

SKN-GPG: SENSITIZER 3.
 SKN-RBT LD50: 2000 MG/KG 3.
 ORL-RAT LD50: >3600 MG/KG 3.
 IHL-RAT LC50: 3.1 MG/L/4H 3.

MUTAGENICITY: INVITRO MUTAGENICITY STUDIES WERE NEGATIVE.

TERATOLOGY (BIRTH DEFECTS): HAS CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS ONLY AT DOSES TOXIC

ALIPHATIC ALCOHOLS, C11-14

ORL-RAT LD50: 17,200 MG/KG 3.
 SKN-RBT LD50: 5600 MG/KG 3.
 SKN-RBT OPEN IRRITATION TEST: 410 MG MILD 3.

SECTION VII - REACTIVITY DATA

Stability: Stable:X Unstable:

Conditions to Avoid: EXPLOSIVE
 PEROXIDES MAY FORM UPON
 PROLONGED STORAGE WITH
 EXCESSIVE EXPOSURE TO AIR AND
 SUNLIGHT.

Incompatibility (Materials to Avoid):

STRONG OXIDIZING AGENTS SUCH AS CHLORINE BLEACH AND CONCENTRATED HYDROGEN PEROXIDE;
 STRONG ACIDS AND BASES; ACID ANHYDRIDES, ALKYLENE OXIDES, HALOGENS, COPPER, BRASS, ALUMINUM,
 MONOMERS, POLYMERIZABLE ESTERS AND HALOGENATED HYDROCARBONS.

Hazardous Decomposition Products:

OXIDES OF CARBON, NITROGEN, SULFUR AND PHOSPHORUS; HYDROGEN CHLORIDE, HYDROGEN SULFIDE,
 ALDEHYDES, FORMALDEHYDE AND AMMONIA.

Hazardous Polymerization:

May Occur:X

Will Not Occur:

Conditions to Avoid: N/A

SECTION VIII - SPILL OR LEAK PROCEDURES**Steps to be Taken if Material is Released or Spilled:**

WEAR APPROPRIATE PROTECTIVE CLOTHING. USE CARE AS SPILLS MAY BE SLIPPERY. DIKE AND CONTAIN SPILL. ABSORB WITH AN INERT MATERIAL AND TRANSFER ALL MATERIAL INTO A PROPERLY LABELED CONTAINER FOR DISPOSAL. PREVENT PRODUCT FROM CONTAMINATING SOIL OR FROM ENTERING SEWAGE AND DRAINAGE SYSTEMS AND BODIES OF WATER. FLUSH AREA WITH WATER.

Waste Disposal Method(s):

DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Neutralizing Agent:

N/A

SECTION IX - SPECIAL PROTECTION INFORMATION**Required Ventilation:**

LOCAL VENTILATION IS RECOMMENDED TO CONTROL EXPOSURE FROM OPERATIONS THAT CAN GENERATE EXCESSIVE LEVELS OF VAPORS OR MISTS. LOCAL VENTILATION IS PREFERRED, BECAUSE IT PREVENTS DISPERSION INTO WORK AREAS BY CONTROLLING IT AT ITS SOURCE.

Respiratory Protection:

RESPIRATORS SHOULD BE SELECTED BY AND USED UNDER THE DIRECTION OF A TRAINED HEALTH AND SAFETY PROFESSIONAL FOLLOWING REQUIREMENTS FOUND IN OSHA'S RESPIRATOR STANDARD (29 CFR

SECTION XI - REGULATORY INFORMATION

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Upper % Limit</u>
GLYCOL ETHERS	N/A	20

Those Ingredients listed above are subject to the reporting requirements of 313 of Title III& of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

CALIFORNIA PROPOSITION 65

WARNING: This product contains the following chemical(s) know to the State of Californiato cause (1)Cancer or (2) Birth Defects or other reproductive harm. THIS PRODUCT CONTAINS FORMALDEHYDE (1) AS A TRACE CONTAMINANT.

SECTION XII - REFERENCES

1. THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS AND BIOLOGICAL EXPOSURE
 2. OSHA PEL.
 3. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES, CCINFODisc, 2002.
 4. VENDOR'S MSDS.
 5. IARC.
-