# Material Safety Data Sheet

## **Section 1 General Information**

Manufacturer:

Zinsser Company, Inc. 173 Belmont Drive Somerset, NJ 08875 (732) 469-8100

Emergency Telephone: Chemtrec (800) 424-9300 Date: December 1, 2006

Product Name: Ready Patch

Codes: 04401 04404 04408 04409 04421 04424 04428 04429

#### **Section 2 Hazardous Ingredients**

Hazardous Component	CAS#	OSHA <u>PEL</u>	ACGIH TLV
VM&P Naphtha	8032-32-4	500 ppm	300 ppm
Mineral Spirits	8052-41-3	500 ppm	100 ppm
Barium Sulfate	7727-43-7	$15 \text{ mg/m}^{3*} (5 \text{ mg/m}^{3**})$	$10 \text{ mg/m}^{3*}$
Kaolin	1332-58-7	$15 \text{ mg/m}^{3*} (5 \text{ mg/m}^{3**})$	$2 \text{ mg/m}^{3*}$
m-Xylene	108-38-3	100 ppm	100 ppm

## Section 3 Hazard Identification

**Emergency Overview**: This material a viscous white paste with a flash point above 200 °F. It is used as a lightweight spackling and patching compound.

#### **Primary Routes of Exposure:**

Eye contact Skin contact

#### **Potential Acute Health Effects:**

**Eye**: May cause eye irritation.

**Skin**: May cause skin irritation.

**Ingestion**: May cause gastrointestinal distress. Ingestion is not considered a significant route of exposure during intended use.

**Inhalation**: May cause respiratory irritation from dust generated by sanding. If signs/symptoms occur, remove person to fresh air. If signs/symptoms persist, consult a physician.

N/A: Not Applicable	N/D: Not Determined	N/E: Not Established	N/R: Not Required	Est.: Estimated
				-

MSDS Code: ReadyPatch MSDS (12-01-06)

Page 1 of 5 pages.

Potential Chronic Health Effects: None Known.

(See also Sections 4, 8, and 11for related information)

#### **Section 4 First Aid Measures**

**Eye contact**: Flush eyes with water for 15 minutes.

**Skin contact**: Wash with soap and water. Get medical attention if symptoms occur.

**Ingestion**: If swallowed, call a physician or poison control center.

**Inhalation**: No specific treatment is necessary since this material is not likely to be hazardous by inhalation. If respiratory irritation occurs due to dust levels generated during sanding, remove person to fresh air. If irritation persists seek medical attention.

**Note to Physician**: This material is basically non-toxic. A small quantity (approximately one-tablespoon) is unlikely to cause harm.

## **Section 5 Fire Fighting Measures**

**Flash Point** (method):  $> 200 \,^{\circ}$  F.

Flammable Limits in Air: Not Determined.

**Extinguishing Media**: The liquid material will not burn. However, the dried film may burn in a fire. Use water spray, dry chemical, or carbon dioxide when fighting fires involving this material.

**Protection of Firefighters**: As in any fire, wear self-contained breathing apparatus in pressure demand mode and full protective gear.

#### **Section 6 Accidental Release Measures**

**Clean Up Methods**: Keep unnecessary people away. Transfer material to containers for recovery or disposal, or absorb with absorbent materials and place into containers for disposal. Keep spill out of sewer and open bodies of water. Floors may be slippery; care should be exercised to avoid falls during clean up operations.

(See also Section 8 for information on Exposure Controls and Personal Protective Equipment)

#### **Section 7 Handling and Storage**

**Handling**: Avoid contact with eyes, skin, and clothing.

**Storage**: Keep from freezing. Keep container closed when not in use.

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

MSDS Code: ReadyPatch MSDS (12-01-06)

## **Section 8 Exposure Controls / Personal Protection**

**Engineering Controls**: If exposure conditions warrant, use mechanical local exhaust ventilation or general dilution ventilation to reduce vapor and/or dust concentrations.

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

MSDS Code: ReadyPatch MSDS (12-01-06)

Page 3 of 5 pages.

## **Section 13 Disposal Considerations**

RCRA Hazardous Waste: No

**Recommended Waste Disposal Method**: This material is not considered hazardous waste under Federal Hazardous Waste Regulations (40CFR 261). However, state and local requirements for waste disposal may be more restrictive or otherwise differ from federal regulations. Chemical additions, processing or otherwise altering this material may render the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Consult all applicable federal, state, and local regulations regarding the proper disposal of this material.

## **Section 14 Transportation Information**

**Regulated by DOT**: Not Regulated.

**DOT Proper Shipping Name**: Paint Products

**UN / NA Number:** N/A

## **Section 15 Regulatory Information**

#### **CERCLA**:

The Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification to the National Response Center for releases of quantities of Hazardous Substances equal to or greater than the reportable quantities (RQs) in 40 CFR 302.4 (for CERCLA 102).

Components present in this product at a levef5.96 Tm/ric19.79Tm0110.0009 Tc-0.000 Tw(equal hderuld es noti

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

Components present in this product at a level which could require reporting under the statute are:

Chemical NameCAS#Maximum Concentration (Wt. %)Xylene1330-20-73 %

#### TSCA:

The components of this mixture are listed in the Toxic Substance Control Act Inventory of Chemical Substances.

This product does not contain any chemicals that require export notification under Section 12(b) of the TSCA regulation.

#### **Section 16 Other Information**

**Legend**: N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required

**STEL**: Short Term Exposure Limit C: OSHA Ceiling Value **PPM**: Parts Per Million **PPB**: Parts Per Billion

**PEL** 

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

MSDS Code: ReadyPatch MSDS (12-01-06)